Technical Product Datasheet



Product identification Article number 20500005 F 6/1 E F15 / V / 0

Product group food conveyor belt horizontal running

Application transport of unit load, dough dispenser, cleaning belt

Industry food, glass and textile industry

Belt construction

Mode of transport

Material conveying side felt

Characteristics conveying side

Color conveying side Cover thickness conveying side

Shore hardness A°

Material traction layer

Number of fabrics

Material running side

Characteristics running side

Color running side

Cover thickness running side

not adhesive

white

1.5 mm

polyester fabric

polyester fabric

slippery

white

uncoated

Product characteristics

Total thickness 2.7 mm (± 0.10 mm)

Belt weight 1.7 kg/m² Standard production width 1,500 mm

Maximum tensile force 80 N/mm

- at 1% elongation (DIN EN ISO 527-1)

Minimum pulley diameter

Minimum pulley diameter backflexing

Knife edge suitable Operation temperatures

Permanently antistatic (DIN EN ISO 21178)

Flammability (DIN EN ISO 340)

Chemical resistance

Complies with FDA

Meets EU regulation for food contact

6 N/mm

30 mm

50 mm

no Min:

-10 °C 14 °F Max: 70 °C 158 °F

no no

oil and grease resistant (see list of resistance)

yes (see declaration of conformity) yes (see declaration of conformity)

Installation terms

Slider bed suitable Carrying rollers suitable yes

Low noise application Accumulation mode

Inclined transportation **Buckling conveyor**

Friction coeff. on slider bed of steel

Friction coeff. on slider bed with friction cover

Troughed installation Cross rigidity

Curved installation

yes

no

no

ves

nο

no

0.15

0.3

no

yes

The listed performance data, information on application and use are only recommendations and were identified under normal conditions and are subject to the changes through continuous development. Since the VIS GmbH has no influence on the specific conditions of use, there can be differences in the data and information. Therefor, no liability can be accepted for the qualification of the product for the specific application

Technical status: 01/2016 - specifications subject to change without notice -

