Joining instruction*



Product identification F 12/2 E V10A / V05NP Article number 20100034

Product group

food conveyor belt


Endless joining

Recommended joining Joining addition Length of fingers Width of fingers double finger joining

 105
 mm
 4,13 inch

 55
 mm
 2,17 inch

 20
 mm
 0,79 inch



Joining material

Joining material conveying side Joining material running side Joining material inside Additional material silicone paper glossy silicone pad NP PVC foil no



heating plate top silicone paper glossy



conveyor belt (conveying site up) PVC foil conveyor belt (conveying site up) silicone pad NP heating plate bottom

Joining parameters

Heating temperature top Heating temperature bottom Heating time

Pressure Note 165 °C 329 °F 165 °C 329 °F

3 minutes 1 bar

use same material for edge demarcation

Alternative joining methods

Finger joining alternative Step joining Wedge joining Mechanical joining single finger joining yes on request yes G003 Alligator RS62

Notes on installation

Loosely assemble the conveyor belt and then tighten until it works seamlessly with full band loading. With no less than an elongation at fitting of 0.3%.

Technical status: 01/19

*mentioned parameters are based on experience in production of endless seamed belt with our tools. By using other tools the parameters can differ. Specifications subject to change without notice.

ww.▼ I S GmbH.eu