

Joining instruction*




Product identification	F 6/1 E U05GST / U0	Article number	20200006
-------------------------------	----------------------------	-----------------------	-----------------

Product group food conveyor belt


Endless joining

Recommended joining	single finger joining	
Joining addition	105 mm	4,13 inch
Length of fingers	70 mm	2,76 inch
Width of fingers	10 mm	0,39 inch



Joining material

Joining material conveying side	silicone pad GST
Joining material running side	silicone pad
Joining material inside	PU foil
Additional material	gauze



heating plate top
silicone pad GST
PU foil
conveyor belt (conveying site up)
conveyor belt (conveying site up)
gauze + PU foil transparent
silicone pad
heating plate bottom

Joining parameters

Heating temperature top	165 °C	329 °F
Heating temperature bottom	165 °C	329 °F
Heating time	2 minutes	
Pressure	1 bar	
Note	use same material for edge demarcation	

Alternative joining methods

Finger joining alternative	no
Step joining	no
Wedge joining	on request
Mechanical joining	yes G001

Notes on installation

Loosely assemble the conveyor belt and then tighten until it works seamlessly with full band loading. With no less than an elongation at fitting of 0.3%.

Technical status: 01/19

*mentioned parameters are based on experience in production of endless seamed belt with our tools. By using other tools the parameters can differ. Specifications subject to change without notice.