Joining instruction*



Product identification Nonwoven 25 NA Article number 20500004

Product group

food conveyor belt

Endless joining

Recommended joining Joining addition Length of fingers Width of fingers single finger joining

 105
 mm
 4,13 inch

 70
 mm
 2,76 inch

 10
 mm
 0,39 inch



Joining material

Joining material conveying side Joining material running side Joining material inside Additional material silicone pad silicone pad 3x PU hotmelt foil

no



heating plate top silicone pad

heating plate bottom



conveyor belt (conveying site up) 3x PU hotmelt foil conveyor belt (conveying site up) silicone pad

Joining parameters

Heating temperature top Heating temperature bottom Heating time

Heating ti Pressure Note 160 °C 320 °F 160 °C 320 °F

2 minutes 1 bar

split the material and put in 3 hotmelt foils, use metal sheet (thickness = belt thickness)

Alternative joining methods

Finger joining alternative Step joining Wedge joining Mechanical joining

no no

on request

yes G002 A40 Alligator RS62

Notes on installation

Loosely assemble the conveyor belt and then tighten until it works seamlessly with full band loading. With no less than an elongation at fitting of 0.3%.

Technical status: 03/19

*mentioned parameters are based on experience in production of endless seamed belt with our tools. By using other tools the parameters can differ. Specifications subject to change without notice.

