

Standard Product Range VIS Flat Belts



Belt type						Running side			Traction layer	Back side			Product characteristics								
Art. No.	Reference				Old reference	Material	Surface	Colour	Material	Material	Surface	Colour	Thickness [mm]	Weight [kg/m ²]	Production width [mm]	1 % elongation [N/mm]	Tensile force [N/mm]	Minimum pulley diameter [mm]	Operation temperatures [°C]	Antistatic	Joining length [mm]
Conveyor Belts																					
30400001	C	4	TG	20	TAS 20/SU	Elastomer	structured	green	Polyamide	Fabric	fabric structure	black	1,9	2,2	500	4	130	30	-20...+100	●	60
30400002	C	5	TG	30	TAS 30/SU	Elastomer	structured	green	Polyamide	Fabric	fabric structure	black	2,6	3,0	500	5	240	40	-20...+100	●	80
30400003	C	5	TG	40	TAS 40/SU	Elastomer	structured	green	Polyamide	Fabric	fabric structure	black	3,5	3,8	500	5	250	50	-20...+100	●	100
30400018	C	5	TG	60	TAS 60/SU	Elastomer	structured	green	Polyamide	Fabric	fabric structure	black	5,8	6,2	500	5	250	120	-20...+100	●	140
30400004	C	5	G	AR T 60	15 TAGRIP 60/SU	Elastomer	supergrip	green	Polyamide	Fabric	fabric structure	black	5,8	5,0	500	5	150	80	-20...+80	●	140
30400005	C	4	G	NO G 23	10 NO	Elastomer	nap	green	Polyamide	Elastomer	smooth	green	2,4	2,2	500	4	125	25	-20...+80		50
30400006	C	4	G	NO T 21	10 NO/UF	Elastomer	nap	green	Polyamide	Fabric	fabric structure	grey	2,3	2,1	500	4	125	25	-20...+80		50
30400007	C	2	PP	12	08 FO	Polyamide	smooth	black	Polyamide	Polyamide	smooth	black	1,2	1,0	500	2	90	30	-20...+80		25
30400008	C	4	TT	10	10 UF	Fabric	fabric structure	grey	Polyamide	Fabric	fabric structure	grey	1,0	0,8	500	4	130	25	-20...+80		35

Remarks:

For all listed products technical data sheets are available on request.

The minimum pulley diameters are determined at room temperature. They are valid for endless heated joinings and correspond to VIS' recommended joinings.

The responsibility for the correct product selection is at the customer. For damage which results from a wrong use of the product, VIS GmbH does not take any responsibility.

Keep transmission belts cool, dry and clean. Protect against dust, direct sun light (UV radiation) and humidity.

Technical specifications to change without notice.